









# SWITCHING ADAPTER PART NUMBER CONFIGURATION

## WALL MOUNT TYPE AC ADAPTER

TRXXX -	X	-	XX		X		XX
Model No.	AC Plug Type		DC Plug Type		OVP Option		DC Cable Length and Type
A : USA 2 Pin			<b>Straight/Inner+Outer-</b>		A: Without OVP Option		01: 720mm
E : Europe 2 Pin			<b>Right Angle/Inner+Outer-</b>		E : With OVP Option		02: 1220mm
U : British 3 Pin			<b>+</b>  <b>-</b>	<b>+</b>  <b>-</b>			03: 1800mm
S : Australia 2 Pin			11 : 5.5 x 2.1 x 12mm	01 : 5.5 x 2.1 x 12mm			11: 720mm with Ferrite Core
			12 : 5.5 x 2.5 x 12mm	02 : 5.5 x 2.5 x 12mm			12: 1220mm with Ferrite Core
			18 : 5.5 x 2.5 x 11mm	17 : 5.5 x 2.1 x 11mm			13: 1800mm with Ferrite Core
			23 : 5.5 x 2.1 x 9.5mm	19 : 5.5 x 2.5 x 10.5mm			
			26 : 5.5 x 2.5 x 9.5mm	20 : 5.5 x 2.5 x 9mm			
			32 : 5.5 x 2.1 x 7.5mm	21 : 5.5 x 2.5 x 9.5mm			
			33 : 5.5 x 2.1 x 11.5mm	24 : 5.5 x 2.1 x 9.5mm			
			35 : 4.0 x 1.7 x 9.5mm	31 : 3.5 x 1.35 x 7.5mm			
			37 : 5.5 x 2.5 x 7.5mm	34 : 5.5 x 2.1 x 11.5mm			
			39 : 3.5 x 1.35 x 9mm	36 : 3.5 x 1.35 x 9mm			
			41 : 3.5 x 1.35 x 7.5mm	40 : 4.0 x 1.7 x 9.5mm			
			45 : 4.75 x 1.7 x 9.5mm	42 : 3.5 x 1.35 x 9.5mm			
			50 : 4.0 x 1.7 x 11mm	46 : 4.0 x 1.7 x 12mm			
				48 : 5 x 1.5 x 9.5mm			
				49 : 2.35 x 0.7 x 9.5mm			
			<b>Straight/Inner-Outer+</b>	<b>Right Angle / Inner-Outer+</b>			
			<b>-</b>  <b>+</b>	<b>-</b>  <b>+</b>			
			05 : 5.5 x 2.1 x 12mm	03 : 5.5 x 2.1 x 12mm			
			13 : 5.5 x 2.1 x 12mm	04 : 5.5 x 2.5 x 12mm			
			14 : 5.5 x 2.5 x 12mm	16 : 5.5 x 2.1 x 11mm			
			27 : 5.5 x 2.5 x 9.5mm	22 : 5.5 x 2.5 x 9.5mm			
				43 : 5.5 x 2.1 x 9.5mm			
				44 : 3.5 x 1.35 x 7.5mm			
				105: 3.5 x 1.05 x 9.5mm			
				111: 3.5 x 1.35 x 9.5mm			
				122: 3.5 x 1.35 x 12mm			
				141: 5.5 x 2.1 x 11mm			
				150: 3.5 x 1.35 x 9mm			
				317: 5.5 x 2.5 x 9mm			

## DESK TOP TYPE AC ADAPTER

TRXXXX -		XX		X		XX
Model No.		DC Plug Type		OVP Option		DC Cable Length and Type
		<b>Straight/Inner+Outer-</b>	<b>Right Angle/Inner+Outer-</b>	A: Without OVP Option		01: 720mm
		<b>+</b>  <b>-</b>	<b>+</b>  <b>-</b>	E : With OVP Option		02: 1220mm
		11 : 5.5 x 2.1 x 12mm	01 : 5.5 x 2.1 x 12mm			03: 1800mm
		12 : 5.5 x 2.5 x 12mm	02 : 5.5 x 2.5 x 12mm			11: 720mm with Ferrite Core
		18 : 5.5 x 2.5 x 11mm	17 : 5.5 x 2.1 x 11mm			12: 1220mm with Ferrite Core
		23 : 5.5 x 2.1 x 9.5mm	19 : 5.5 x 2.5 x 10.5mm			13: 1800mm with Ferrite Core
		26 : 5.5 x 2.5 x 9.5mm	20 : 5.5 x 2.5 x 9mm			
		32 : 5.5 x 2.1 x 7.5mm	21 : 5.5 x 2.5 x 9.5mm			
		33 : 5.5 x 2.1 x 11.5mm	24 : 5.5 x 2.1 x 9.5mm			
		35 : 4.0 x 1.7 x 9.5mm	31 : 3.5 x 1.35 x 7.5mm			
		37 : 5.5 x 2.5 x 7.5mm	34 : 5.5 x 2.1 x 11.5mm			
		39 : 3.5 x 1.35 x 9mm	36 : 3.5 x 1.35 x 9mm			
		41 : 3.5 x 1.35 x 7.5mm	40 : 4.0 x 1.7 x 9.5mm			
		45 : 4.75 x 1.7 x 9.5mm	42 : 3.5 x 1.35 x 9.5mm			
		50 : 4.0 x 1.7 x 11mm	46 : 4.0 x 1.7 x 12mm			
			48 : 5 x 1.5 x 9.5mm			
			49 : 2.35 x 0.7 x 9.5mm			
		<b>Straight/Inner-Outer+</b>	<b>Right Angle/Inner-Outer+</b>			
		<b>-</b>  <b>+</b>	<b>-</b>  <b>+</b>			
		05 : 5.5 x 2.1 x 12mm	03 : 5.5 x 2.1 x 12mm			
		13 : 5.5 x 2.1 x 12mm	04 : 5.5 x 2.5 x 12mm			
		14 : 5.5 x 2.5 x 12mm	16 : 5.5 x 2.1 x 11mm			
		27 : 5.5 x 2.5 x 9.5mm	22 : 5.5 x 2.5 x 9.5mm			
			43 : 5.5 x 2.1 x 9.5mm			
			44 : 3.5 x 1.35 x 7.5mm			

Cincon offers a wide variety of DC plugs for every customers.

Please contact your distributor or E-Mail [sales@cincon.com.tw](mailto:sales@cincon.com.tw) for more information.